#### (12) IN ACTIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization International Bureau



#### (43) International Publication Date 15 July 2004 (15.07.2004)

#### PCT

## (10) International Publication Number WO 2004/058013 A1

(51) International Patent Classification7:

A47G 25/40

(21) International Application Number:

PCT/GB2002/005942

(22) International Filing Date:

30 December 2002 (30.12.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant and

(72) Inventor: NATHANMANNA, Ameyrtharatnarajah [LK/GB]; 224 Ray Lodge Road, Woodford Green, London, Greater London IG8 7PE (GB).

(74) Agent: EDER, Ephry; B. EDER & CO, 39 Cranbrook Road, Ilford, Essex IG1 4PA (GB). (81) Designated States (national): AU, CA, CN, CU, ID, IL, IN, JP, KR, LK, NO, NZ, PL, SG, US.

(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

Declaration under Rule 4.17:


as to the identity of the inventor (Rule 4.17(i)) for all designations

#### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

### (54) Title: FOLDABLE CLOTHES HANGER



(57) Abstract: A foldable clothes hanger comprising two foldable arms (17,22) mounted pivotably on a common axis (8), each arm (17,22) having a part provided with a toothed arcuate rack (14,19) engaging a pinion (24,23) that is mounted pivotally on an adjacent parallel axis (9). Each of the arms (17,22) carries a generally arcuate limb provided with latch means (13,18), and the hanger comprises catch means (5,4) to engage with the latch means (13,18). Means (3) are provided to effect resilient engagement between the latch means (13,18) and the catch means (13,18), and release means (6,28), e.g. comprising an integral pushbutton (28), are manually operable to counter the resilient engagement and permit disengagement of the latch means (13,18) and the catch means (5,4).